



Printing format

- Printable area Ø 117 mm
- Centre hole must be recessed.
- Please don't create any bleed!
- Please create the document containing one label only.

Colours

Euro scale (4c), Spot colours (HKS, Pantone)

Pictures

- **Please deliver all used pictures!**
- File format: Tif or EPS
- Resolution: 300dpi
- Modus CMYK or Spot colours

Fonts

Please create outlines of all used fonts or deliver all used fonts.

File formats MAC

- Freehand (up to MX)
- QuarkXPress 6
- Indesign CS2
- Adobe Acrobat 4.0 (printable PDF)

File formats PC

- Freehand (up to MX)
- QuarkXPress 6
- Indesign CS2
- Adobe Acrobat 4.0 (printable PDF)

Data delivery

- ISDN (MAC Leonardo): +49 40 253339-20
- CD-ROM (Please attach printout!)

Attention!

The colour intensity, image quality, text sharpness and screen quality of the proofs, Chromalins or other offset processes normally deviate from the silk-screen print. Smooth screen gradients are not possible.

Informations for Printing of CD's (Silk-Screen Printing)

- File formats - page 1
- Films: - Positive, right reading, emulsion side up
- Printing Format: - Look at the specification (page 1)
- Format-marks: - 1 cm out of the printing format
- Sreen Count: - 34 line/cm, 48 line/cm (recommendation), 54 line/cm
- tonal range approx. 15-85%
- Dot Form: elliptical dots
- Screen Angle: - Colour: C M Y K
- Angle: 75° 15° 0° 45°
- Line Sizes: - 0,10 mm minimum, negativ 0,15 mm minimum
- Text Sizes: - 5 point minimum , negativ 6 point minimum
- Printing Colours: - CMYK, Pantone, HKS